


Favorable action is respectfully solicited.

ADDITIONAL FEE

Please charge any insufficiency of fees, or credit any excess, to Deposit Account  
No. 14-1263.

Respectfully submitted,


NORRIS, McLAUGHLIN & MARCUS, P.A.

By   
William C. Gerstenzang  
Reg. No. 27,552

220 East 42nd Street - 30th Floor  
New York, New York 10017  
(212) 808-0700

I hereby certify that this paper is being deposited with the  
United States Postal Service as Express Mail, Label No.  
EL767491742US to: BOX PATENT APPLICATIONS, Hon.  
Assistant Commissioner of Patents, Washington, D.C. 20231  
on December 1, 2000.

Norris McLaughlin & Marcus, P.A.

By:   
Date: 12/1/00

007027 64332460

MARKED-UP COPY OF AMENDED CLAIM,  
SHOWING CHANGES RELATIVE TO PREVIOUS VERSION

Claim 1 (amended). An adhesive tape with adhesive front side and nonadhesive rear side and two long edges for flying reel change, having

- a) a film backing (P1)[,] having a frong side and a rear side and which is coated on [one side -] the frong side [-] with a self-adhesive composition (N1),
- b) part of the nonadhesive rear side of the film backing (P1) being equipped with a double-sided adhesive tape (DO) which has, on one side, a cleavable system (P2) coated on both sides with self-adhesive composition (N2, N3), wherein
- c) the double-sided adhesive tape (DO) is arrnaged at a distance (V) of 0-15 mm, [especially 0.5 to 15 mm,] from one long edge (LK) of the adhesive tape.

Claim 2 (amended). The adhesive tape as claimed in claim [1] 13, wherein the distance (V) is 0-7 mm [especially 1 to 7 mm].

Claim 3 (amended). The adhesive tape as claimed in claim [1] 2, wherein the distance (V) is 1.5 to 3.5 mm.

Claim 9 (amended). The adhesive tape as claimed in claim 1, wherein the double-sided adhesive tape (DO) is 3 to 35 mm side[, especially 6 to 12 mm wide].

Claim 10 (amended). The adhesive tape as claimed in claim 1, wherein the cleavage strength of the cleavable system (P2) is 20 to 70 cN/cm[, especially 22 to 60 cN/cm, very particularly 25 to 50 cN/cm].

Claim 11 (amended). A splicing method, in which an adhesive tape as claimed in [one

0972339 "120100  
007027" 6632260

of claims 1-10] Claim 1 is partly stuck behind the top paper or film web of a reel, while the double-sided adhesive tape on the rear side of the adhesive tape is [for its part] stuck to the web beneath it and therefore secures the top web, firstly only part of the release material [possibly] optionally located on the self-adhesive composition being pulled off, so that that part of the self-adhesive composition needed for the splicing method is still masked with release material and, in this state, the reel has no free adhesive area, after which, in order to prepare for the splicing method finally, any remaining release material still present is removed, whereupon the new reel equipped in this way is placed beside an old reel which has been almost completely unwound and is to be replaced, and is accelerated to the same rotary speed as said old reel and is then pressed against the old paper or film web, the exposed self-adhesive composition of the adhesive tape sticking to the old paper or film web at essentially equal speeds of the paper or film webs, while at the same time the cleavable system cleaves and, with its remains, nonadhesively masks both self-adhesive compositions which were coated on said system.

Claim 12 (amended). The splicing method as claimed in claim 11, wherein the adhesive tape is bonded to the running web at right angles or [else] at an acute angle of up to 45°[, especially up to 15°].